

# modero

## Wanted Poster Type: XKS340-40



### System options

Description	Price
<b>Climate test chamber XKS340-40</b> Including factory calibration in Oberhausen, one NW 80 feedthrough, one shelf Screen program controller, computer interface, test object condensation protection, documentation	<b>Base price [UVP]</b>  <b>29,300.00 €</b>
<b>Test room window (450 x 500 mm)</b> Multiple pane set in the test room door	Included
<b>Machine feet</b> , height-adjustable machine feet with castors	Included
<b>Test room lighting</b> switchable via controller	Included
<b>Execution NW100</b> with silicone stopper in the middle of the right one	400.00 €
Test room side wall	Included
<b>Factory calibration</b> with 3 temperature / humidity points; -30 °C; + 120 °C and 85 °C at 85 %rH or according to customer specifications	Included
<b>Regulation SE-702</b> , Powerful computer built for industrial use; TFT LCD 17.8 cm (7 ") with capacitive multi-touch screen; Data recorder with multi-touch operation; (optional); Capacitive touch with gesture control; Client / server structure High quality finish	2,500.00 € Included
Air-cooled chiller (no water supply necessary)	682.00 € Included
Capacitive humidity measurement instead of the psychrometer	1,640.00 € Included
<b>Total price with this configuration:</b>	<b>34,492.00 €</b>
<b>Offer price with this configuration</b> <b>(available at short notice &amp; price on our website):</b>	<b>32,100.00 €</b>
<b>More options:</b>	
Additional shelf	180.00 €
Adsorption dryer	2,530.00 €
Additional feedthrough NW 50 with silicone stopper	350.00 €
Additional feedthrough NW 125 with silicone stopper	425.00 €
Additional feedthrough NW 150 with silicone stopper	450.00 €
Demineralization system	2,470.00 €



## Dimensions

<b>Temperature range</b>	-40 °C ... +150 °C
Achievable final temperature	+180 °C
<b>Temperature deviation</b>	
Temporally in the range from -40 °C to +150 °C	±0.2 K ... ±1.0 K
Spatially in the range from -40 °C to +150 °C	±0.1 K ... ±2.0 K
<b>Rate of temperature change according to EN 60068-3-5</b>	
Cool	approx. 4.5 K/min
Heat	approx. 5.5 K/min
<b>Humidity range</b>	10 %rH ... 98 %rH
Humidity temperature range	+10 °C ... +90 °C
Humidity deviation	±0.5 %rH ... ±5.0 %rH
Dew point temperature range	+4 °C ... +88 °C
Connected load, approx.	14 kW
Power consumption, approx.	27 A

## Dimensions

	Width	Depth	Height	Volume
Test room	600 mm	745 mm	750 mm	approx. 340 l
Outside	870 mm	1700 mm	1715 mm	



## Commercial information

### Sales, Delivery, Payment and Assembly Conditions for Germany

<b>Deals</b>	We give free and non-binding on the basis of our general Terms and Condition.
<b>Offer Validity</b>	6 weeks (from 11.08.2020).
<b>Pricing</b>	EXW RS-Simulatoren Prüf- & Messtechnik GmbH, Niebuhrstraße 59, 46049 Oberhausen (Incoterms®2020).
<b>VAT</b>	Is not included in the prices.
<b>Delivery time</b>	According to agreement and stock.
<b>Delivery terms</b>	Our delivery conditions are part of our offers.
<b>Payment terms</b>	100 % after delivery. Payable 10 days after the invoice date. Total amount, however, no later than 30 days after delivery if the acceptance is delayed for reasons for which RS-Simulatoren in not responsible.
<b>Retention of title</b>	The delivered goods remain until they have been paid for in full, also to third parties.
<b>Guarantee</b>	2 years with a fee-based maintenance in the 12 <sup>th</sup> month (only valid within Germany, otherwise our separate warranty conditions apply abroad). Maintenance and repairs are only permitted by employees of RS-Simulatoren or a company authorized by RS-Simulatoren. Failure to observe these points will invalidate any warranty and liability claims.
<b>Installation and commissioning</b>	Calculation is based on the time and effort.
<b>Factory standard</b>	If there are company standard, we would be happy to expand the range On the basis of them.
<b>Foreign countries</b>	The terms of Sale, Delivery, Payment and Installation must be requested separately.
<b>Technical changes</b>	Are reserved.

